



**Hibiscus Plc**  
THE PRINTING PLANT

Hibiscus Plc.  
Hudswell Road,  
Leeds LS10 1AG.  
Tel: 44 (0) 113 242 4272  
Fax: 44 (0) 113 242 4230

**SPECIFICATION: Rigid PVC (silk screen)**

Labels silk screen printed onto Rigid PVC supplied as cut singles with or without overlamineate.

**1. Face Material**

Opaque rigid PVC film with high gloss surface.  
Thickness: 240, 480 or 700 micron

**2. Inks**

Silk screen printing inks are limited to Coates Vynaglaze and Sericol Polyplast or Plastijet. All inks have a high gloss finish, good adhesion and flexibility. Coates inks have a rating of 7-8 on the Blue Wool Scale and under accelerated weathering tests, conducted in accordance with BS3900 Part F3 indicate an expected outdoor life of approximately 5 years. Sericol inks, under accelerated weathering tests conducted in accordance with BS3900 Part F3 indicate an expected outdoor life of 2 to 3 years.

**3. Overlamination (where applicable)**

25 or 30 micron thick polypropylene film coated with age resistant acrylic adhesive.

**4. Guillotining**

Unless specifically agreed prior to manufacture, all silk screen printed labels are guillotined to a standard tolerance of  $\pm 2$ mm.

**5. Inspection Status**

All labels are inspected visually on an individual basis. Labels are bundled into 100 lots unless specifically requested by a customer.

**NOTE** - The values given in this specification are typical, the information being given in good faith but without warranty.

**Authorised by :** ..... **Date :** .....

**SPEC: Rigid PVC (silk screen). doc**

**Updated Feb 2000**



Directors: B.S. KILLERBY, B.Sc.(Hons.), D. KILLERBY, J.C. KILLERBY, B.Sc.(Econ.)  
Reg. No. 1557744 (England)



www.stock-xpress.com  
www.hibiscus-plc.com  
email: enquiries@hibiscus-plc.com